

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) An optical device comprising:
 - an input fiber for inputting an input optical signal;
 - an output fiber for outputting an output optical signal;
 - an optical path between said input fiber and said output fiber;
 - a substrate comprising at least one step with predefined parameters, said at least one step being disposed in part of said optical path and adding a phase shift to light passing therethrough; and
 - a variable phase shifting element controlled by an applied signal, disposed serially with said at least one step in said part of said optical path, and pixilated such that it shifts the phase of light passing through at least a portion of said part of said optical path;
 - such that the optical interference between light traversing that part of said optical path containing said at least one step and light traversing those parts of said optical path not containing said at least one step results in a wavelength dependent transmission through said device.
2. (Currently amended) An optical device according to claim 1 and wherein the phase ~~shift~~ shifts in said part of said optical path containing said at least one step ~~is~~ are selected such that the said device has a predetermined spectral transmission profile.
3. (Cancelled)
4. (Currently amended) An optical device according to claim ~~2~~1, wherein said variable phase shifting element is a liquid crystal device.

5. (Currently amended) An optical device according to claim 21, wherein said input fiber and said output fiber are disposed such that light passes from said input fiber to said output fiber by transmission through said optical path.

6. (Currently amended) An optical device according to claim 21, and also comprising a reflecting surface associated with said substrate, and wherein said input fiber and said output fiber are disposed such that light undergoes reflection between them.

7. (Currently amended) An optical device according to claim 21, and also comprising a circulator and a reflecting surface, and wherein said input fiber and said output fiber are connected to two ports of said circulator, and said substrate and associated reflecting surface are disposed at a third port of said circulator.

8. (Currently amended) An optical device according to claim 21, and operative as a gain equalizer.

9. (Currently amended) An optical device according to claim 21, and wherein said parameters are at least one of the optical cross section and the height of said at least one step.

10. (Currently amended) An optical device according to claim 21, and wherein said applied signal is adjusted according to the spectral profile of said output optical signal, such that said optical device modifies the spectral transmission profile of said optical path dynamically.

11. (Original) An optical device according to claim 10, and also comprising a channel monitor monitoring said output signal, and wherein said applied signal is obtained from said channel monitor.

17. (Original) A method according to claim 14, wherein said controllable phase shifting element is a liquid crystal device.

18. (Original) A method according to claim 14, wherein said input fiber and said output fibers are disposed such that light passes from said input fiber to said output fiber by transmission through said optical path.

19. (Original) A method according to claim 14, and also comprising the additional step of providing a reflecting surface associated with said substrate, and disposing said input fiber and said output fibers such that light undergoes reflection between them.

20. (Original) A method according to claim 14, and also comprising the additional steps of providing a circulator and a reflecting surface, and connecting said input fiber and said output fiber to two ports of said circulator, and said substrate and associated reflecting surface to a third port of said circulator.

21. (Original) A method according to claim 14, and wherein said applied signal is adjusted according to the spectral profile of said output optical signal, such that said optical device modifies the spectral transmission profile of said optical path dynamically.

22. (Original) A method according to claim 21 and also comprising the step of channel monitoring said output signal, and wherein said applied signal is derived from said channel monitoring.

23. (Original) A method according to claim 21, and wherein said step of adjusting said applied signal compensates for changes in the spectral profile of said input signal dynamically.

24. (Original) A method according to claim 21, and also comprising the step of

